# AVer Cam530 Camera

## Full HD 1080p 60fps Plug & Play Camera for Multiple Businesses

### Package Contents

- Camera
- Remote control
- 5m USB cable to PC (USB 2.0 mini B to PC)
- 3m HDMI cable
- Power supply
- Quick-start guide
- Tabletop/wall/ceiling mount
- 6.35mm tripod mounting screw
- Velcro
- Mini DIN8 to RS232 adapter

#### Camera

- Full HD 1080p
- Pan: ±130°; 0.45° step
- Tilt: +90°/-25°; 0.25° step
- Field of view (H):  $72.5^{\circ}$  (wide) ~  $6.3^{\circ}$  (tele)
- Sensor: 1/2.8 low lux CMOS 2M pixel
- Resolution: full HD 1080p (1920x1080), HD 720p (1280x720), PAL (1024x576), VGA (640x480), QVGA (320x240), QQVGA (160x120) at 60fps, 30fps and 15fps
- . Scan: progressive
- Lens zoom: 12X true optical zoom .
- . Lens focal length: 3.9mm (wide) ~ 47.3mm (tele)
- Lens F#: 1.8 (wide) ~ 2.8 (tele)
- Auto Iris
- S/N ratio: >50dB
- Minimum illumination: 1 lx (50 IRE, F1.6, . shutter 1/30)
- 2D and 3D Denoise .
- **Backlight Compensation**
- . Flip, mirror
- Minimum working distance: 1 meter
- Include table/wall/ceiling mount
- Kensington slot

#### **Remote Control**

- IR (Infrared)
- 10 camera presets (100 presets via VISCA)

#### System Requirements\*

- Windows 7/8/8.1/10
- Mac OS X 10.7 or higher
- Google Chromebook version 29.0.1547.70, Platform 4319.79.0

#### Hardware Requirements\*

- 2.4 GHz Intel<sup>®</sup> Core 2 Duo processor
- 2 GB RAM or more
- Hard drive space for recorded videos

- USB 2.0 port

#### **Power Supply**

- AC 100V ~ 240V
- Consumption: EIAJ 12, 4A

#### **Environmental Data**

- Physical characteristics: 0~40°C
- Operation humidity: 20%~80%
- Storage temperature: -20~60°C
- Storage humidity: 20%~80%

#### **Physical Characteristics**

- Package dimensions: 370 x 252 x 275mm
- Package weight: 4.16kg/9.17lbs
- Camera: 180 x 140 x 182mm/1.5kg
- Remote control: 200 x 50 x 20mm/0.091kg

#### **Compliance and Tools**

- YUV, MJPEG, H.264 SVC, AVC (high and base profile)
- Multi-stream capable
- **USB 2.0**
- UVC (USB Video Class) 1.1 with H.264 extension
- VISCA via RS232
- **HDMI 1.3**
- **DIP Switch**
- Downloadable diagnostic tool, field firmware upgrade tool, App for advanced features and settings

#### PTZApp

- Free download on Windows® and Mac® computers
- Compatible with Skype<sup>™</sup> Plugin for answering and hanging up via remote control
- Upgrade firmware automatically or manually
- Control camera
- Set parameters and adjust camera image
- **Diagnose operating status**
- View live video

### Warranty\*\*

- 3-year: camera
- 1-year: accessories

\* For Full HD support, please check with your software application provider for system/hardware requirements. \*\* Please register online to receive free 2 year warranty extension. For detailed warranty information, please contact an AVer representative.

All rights of this object belong to AVer Information Inc. Reproduced or transmitted in any form or by any means without the prior written permission of AVer Information Inc. is prohibited. All information or specifications are subject to change without prior notice. "AVer" is a trademark owned by AVer Information Inc. Other trademarks used herein for description purpose only belong to each of their companies. Version 1.1 (201603)



# **Product Datasheet**



**Hardware Specifications** 





Back panel



© 2016 AVer Information Inc. All rights reserved.

All rights of this object belong to AVer Information Inc. Reproduced or transmitted in any form or by any means without the prior written permission of AVer Information Inc. is prohibited. All information or specifications are subject to change without prior notice. "AVer" is a trademark owned by AVer Information Inc. Other trademarks used herein for description purpose only belong to each of their companies. Version 1.1 (201603)

