

ACCESSORIES & PACKAGES



1

TransMount Image Transmission Transmitter



2

TransMount PowerPlus Battery Pack



3

TransMount 3S EasySling Handle



4

TransMount CRANE 3S SmartSling Handle



5

TransMount Phone Holder with Crown Gear



6

TransMount Servo Zoom/Focus Motor (Max)



7

TransMount Servo Focus Motor (Lite)



8

Extension Arm and Rubber Cover



9

HDMI Cable A: HDMI Mini to HDMI Micro
HDMI Cable B: HDMI Mini to HDMI Mini
HDMI Cable C: HDMI Mini to HDMI



10

TransMount Handheld Tripod



CRANE 3S-E

3 8 9



CRANE 3S

4 8 9



CRANE 3S PRO

1 2 3 4 5 6 7 8 9 10

CRANE 3S Specs

Operation Voltage	9.8 V-25.2 V
Output Voltage	5 V
Operation Time	12 h
Operation Temperature	-10°C-45°C
Payload	600 g- 6500 g
Tilt Angle Range	360°
Roll Angle Range	330°
Pan Angle Range	360°



ZHIYUN-TECH.COM

Guilin Zhishen Information Technology Co., Ltd. reserves the right to change product design and specifications, including but not limited to size, color, etc. All information contained herein has been carefully checked to ensure accuracy. * Camera is not included in the product package. For more package information, please refer to ZHIYUN's official platforms.



ZY PLAY ZY PLAY

LIGHTCOLLECTOR

CRANE 3

MISSION DELIVERED

- Professional 3-Axis Stabilizer -



/ Reengineered for More Ambitious Camera Setups
/ Extendable Arm. Greater Flexibility
/ Modular Design. Versatile Shooting

CRANE 3

Professional 3-Axis Stabilizer

From intense chasing shoot to studio filming, different types of shooting environment require both high capacity and flexibility of equipment. Bearing filmmakers in mind, ZHIYUN felt the Crane series can be even better to adapt to strict and unpredictable filming environment. Now introducing the new CRANE 3S, the legendary gimbal built on a heritage of innovation with magnificent motors and brand new modular design, which aims for wider application and intuitive control.




MISSION DELIVERED

FEATURES



Reengineered for More Ambitious Camera setups

It is not simply an upgrade but reconstruction. CRANE 3S is constructed with brand new SUPER motors which allow for Max. 6.5kg payload for a wide range of camera setups.




Extendable Arm. Greater Flexibility

An extension module which comes standard with CRANE 3S can be attached onto horizontal arm for mounting larger setups.



Modular Design. Versatile Shooting

You can either mount EasySling handle to extend the grip for more comfort upright & underslung operation, or choose to mount SmartSling handle featuring an intuitive control panel and OLED screen for intuitive control.



Properly Calculated 55°: Broader Vision

The properly 55° tilted roll axis is designed for unblocked view and allows enough space to mount large cinema camera combos.



Improved Zoom & Focus System

To meet the needs of cinematography, larger lens supports are added into the zoom & focus system. Zooming can be realized synchronously through SmartSling Handle.



SyncMotion: Visualized Control

For the first time in the industry, a visualized remote motion control system is introduced - ViaTouch 2.0. Filmmakers will be able to motion control the gimbal while monitoring shots via smartphones or monitors.




Cross-Compatibility. You can Imagine

With multiple thread holes of different sizes provided on both stabilizer and handle, CRANE 3S boasts cross-compatibility with a wide range of accessories such as motorized dolly, jib, cable cam, and Easyrig, satisfying various challenging shooting tasks.



Zero Swinging. Hero Security

The reinvented locking system can lock the three axes without noticeable swinging. The modular design is integrated with double locks to ensure the setup is 100% safe on the gimbal during traveling or storage.



Continuous Uptime Supported by PowerPlus

The DC-IN port supports up to 25.2V input for direct charging. PowerPlus Battery Pack can house 6*18650 batteries, giving more strength to your gimbal to adapt to constant intense motions, and serving as a compact yet fast-charging power bank for your devices.