HOLLYLAND
For a better view!

2018 New Series
COSMO 600

COSMO 600

600FT WIRELESS VIDEO TRANSMISSION WITH INTERNAL ANTENNA

STRONG, FLEXIBILITY, LIGHTNESS - THESE ARE THE FIRST IMPRESSIONS THAT MAKE COSMO 600 STAND OUT FROM THE PACK.

Copyright © Hollyland Technology Co.,Ltd

Features

- Transmission Range: 600ft
- Channel Selection:0-4/Outside USA:0-9
- USB Firmware Upgrade
- No Compression, No Latency
- Point to Point & Broadcast Mode
- 3G-SDI In/Loop Out/, HDMI In/Out
- 5GHz ISM Frequency Band
- Built-in Antennas in Receiver
- 3G-SDI Level B
- Support Timecode& Trigger

Packing List

Hard Case*1

5 GHz Antennas*3

Magic Arm*1

Crab Clamp*1

DC Conversion Cables*2

Transmitter*1

Receiver*1

User Manual*1

Mushroom Antennas*2

Spec

	Transmitter	Receiver
Interface	SDI input (BNC female); SDI loop out (BNC female) HDMI input (Type A female);2 Antenna port (RP–SMA male) DC input (4pin LEMO female); Mini USB port; 3.5mm Analog invoice input port	SDI1 output; SDI2 output; HDMI output(Type A female); DC input(4pin LEMO female); Mini USB port
Supply Voltage Range	7–36V DC	7–36V DC
Power Consumption	<6W	<8W
Weight	260g	460g
Size	(L xWxH):126.5x 70 x 25mm, not include antennas and battery plate	(LxWxH):158.8x 94 x 25mm, not include antennas and battery plate
Input Video Format	HDMI:480p60,576p50,720p50/59.94/60, 1080i50/59.94/60, 1080p23.98/24/25/29.9/30/50/59.94/60; HDMI Type A; SDI:3G, HD, and SD–SDI (auto–selected); SMPTE–259/274/292/296/372/424/425; 1x BNC; 1x BNC Loopout;	/
Output Video Format	/	HDMI:480p60,576p50,720p50/59.94/60, 1080i50/59.94/60, 1080p23.98/24/25/29.9/30/50/59.94/60; HDMI Type A; SDI:3G, HD, and SD–SDI (auto–selected); SMPTE–259/274/292/296/372/424/425; 2x BNC output;
Input Audio	SDI embedded 2 channel 24 bit/48KHz	/
Output Audio	/	SDI embedded 2 channel 24 bit/48KHz
Frequency Band	5.1–5.9GHz,configurable with China, North America, Europe,etc	5.1–5.9GHz,configurable with China, North America, Europe,etc
Modulation Mode	OFDM–16QAM	OFDM–16QAM
Transmission Power	Maximum 17dBm	/
Receiver Sensitivity	/	–75dBm
Occupied Bandwidth	40MHz	40MHz