

MARS 300

300FT Dual HDMI Wireless HD Video Transmission System



Features

- Transmission Range: 300ft+
- Dual HDMI Input / Output
- No Stagnation, No Trailing, No Mosaic
- USB Firmware Upgrade
- Point to Point
- 5GHz Frequency Band
- Compact and Lightweight
- Easy to Install
- Working Voltage:6-16VDC

Highlights



Compact & Lightweight



Easy to Install



Dual HDMI ports



Strong Anti-interference

Packing List



Antennas*5



Cold Shoe*1



User Manual*1



DC Adapter*1



Hard Case*1



Transmitter*1



Receiver*1



Screw Fitting*1



Application



Monitor



Receiver



300ft



Transmitter



Camera

| | Transmitter | Receiver |
|-----------------------------------|---|--|
| Interface | HDMI Input Loop Out (Type A female) 2 Antenna port (RP-SMA male) DC Input, Micro USB Pairing Button, Channel Selection Button | HDMI Output 1, Output 2 (Type A female) 2 Antenna port (RP-SMA male) DC Input, Micro USB Pairing Button, Channel Selection Button |
| Power Supply Voltage Range | 6-16V DC | 6-16V DC |
| Power Consumption | <6W | <5W |
| Weight | 186g | 186g |
| Size | (L x W x H): 105*62*22mm, not include antennas and battery plate | (L x W x H): 105*62*22mm, not include antennas and battery plate |
| Input Video Format | HDMI: 480P@60Hz, 576P@50Hz, 720P@50/60Hz 1080i@50/60 Hz 1080P@30/50/60 Hz | / |
| Output Video Format | / | HDMI: 480P@60Hz, 576P@50Hz, 720P@50/60 Hz 1080i@50/60 Hz 1080P@30/50/60 Hz |
| Frequency Band | 5GHz | / |
| Transmission Power | 17dBm | / |
| Transmission Latency | 50ms | / |
| Receiving Sensitivity | / | -80dB |

