



Mevo Start is the simple, all-in-one solution for taking your content live. Share your event from start to finish - without cables or battery packs - with up to 6 hours of built-in battery life. Stream live to every major platform instantly with the Mevo app. When it's worth sharing, it's worth sharing right.

- Up to 6 hours of streaming/recording
- 1080p encoding in HEVC or H.264
- 802.11ac MIMO Wi-Fi + dual antennas
- Wide angle low distortion lens
- 3 MEMS mics with spatial processing
- Built-in thread for mic/tripod stand
- NDI® video output enabled

What's included?

- 1 Mevo Start video camera
- 1 6.5 ft (2m) USB-C to USB-A cable
- 1 Microfiber lens cloth

Mevo Start - Cámara de Streaming para Eventos Directo por APP



Mevo Start BATTERY Up to 6 hours of battery life

SENSOR Sony® 1080p Sensor (IMX307)

PROCESSOR & ENCODER (SOC) Ambarella H22

SENSOR RESOLUTION 2.07 Megapixels

CAPTURE RESOLUTION 1080p - 1920 x 1080

ASPECT RATIO 16:9

FRAME RATE 30fps

VIDEO (MP4 RECORDING ONLY)

1080p30 at 20Mbps

720p30 at 10Mbps

VIDEO (STREAMING)

1080p30 up to 6Mbps

720p30 up to 3.5Mbps

480p30 up to 1.5Mbps

360p30 up to 1Mbps

NOTES

*Periscope/Twitter maximum streaming resolution is limited at 720p

*Ethernet streaming requires Mevo Start Ethernet Power Adapter

VIDEO CODEC H.264 and HEVC recording up to 1080P

ELECTRONIC IMAGE STABILIZATION Yes

VERTICAL IMAGE FLIP Yes

HIGH-DYNAMIC-RANGE IMAGING Yes

VIDEO OUTPUT NDI® Enabled

BUILT-IN AUDIO Three MEMS microphone array with Fraunhofer upHear® Spatial Microphone Processing

EXTERNAL AUDIO INPUT

- Directly into 3.5mm aux input plug on camera
- Via USB Audio interface to USB-C connector
- Via mic plugged into mobile device
- Via Mevo Mic app

AUDIO MIXER Control external audio source selection and gain through the Mevo app. Stereo/Mono, Meter, Gain control, supports multiple sources

AUDIO CODEC AAC - 48kHz, 16-bits

WI-FI 802.11ac @ 2.4Ghz / 5GHz. 2x2 MIMO, dual antennas Access point mode or join an existing Wi-Fi network

WI-FI NETWORK REQUIRED No, the camera can generate its own network (access point) and stream via the mobile LTE connection

BLUETOOTH Bluetooth 4.1 - BT and BLE compatible

ETHERNET With Mevo Start Ethernet Adapter accessory. Also supports charging via PoE (Power over Ethernet)

LTE Via Mobile phone when using Mevo Start in hotspot mode

STREAMING BANDWIDTH REQUIREMENTS

Full HD - Up to 6 Mbps (At least 3 Mbps of steady upload speed recommended)

HD - Up to 3.5 Mbps (At least 2 Mbps of steady upload speed recommended)

SD (Standard Definition) - Up to 1.5 Mbps (at least 800 kbps of steady upload speed recommended).

Check your connection using Speedtest.net before purchasing Mevo for live streaming.

LIVE STREAMING MODES

(a) Via mobile when using camera access point mode

(b) Direct from camera when joining a Wi-Fi access point

(c) Hardwire via Ethernet when using Mevo Start Ethernet Adapter accessory

RTMP SUPPORT Yes

HEIGHT 3 in (7.55 cm)

WIDTH / DIAMETER 1.3 in (3.4 cm)

LENGTH 3.4 in (8.7 cm)

WEIGHT 8.2 oz (232 g)

COLOR Black

INTERFACES PROVIDED USB-C, micro SD slot

WATER RESISTANT No

EXPOSURE METERING Spot

WHITE BALANCE Auto or presets

WHITE BALANCE PRESETS

1-Incandescent, 2-Sunny, 3-Cloudy, 4-Fluorescent

EXPOSURE MODES Auto with compensation option

EXPOSURE COMPENSATION -2, -1.5, -1.0, -0.5, 0.0, 0.5, 1.0, 1.5, 2.0

CAMERA LENS TYPE low distortion, 8 elements, f2.8, Focal length 3.6mm

FIELD OF VIEW 83.7 degrees (diagonal)

FIELD OF VIEW OPTIONS N/A

FOCUS ADJUSTMENT Fixed

LOW LUX / NIGHT MODE No

CAMCORDER MEDIA TYPE Flash (Removable)

MEMORY CARD COMPATIBILITY Micro SD (SD, SDHC, SDXC)

MEMORY INCLUDED Not Included

BUTTON One on back of camera. Turn on-off, Start/stop streaming and/or recording (configurable)

INDICATOR Front RGB LED tally light & four white battery indicator LEDs

SCREEN, PREVIEW AND CONFIGURATION Via required mobile app

DESKTOP Via Livestream Studio

INCLUDED ACCESSORIES Charging Cable, Microfiber lens cloth

UNDERWATER DEPTH N/A

LANGUAGE English

SIX-AXIS MOTION SENSOR Yes

OPERATING TEMPERATURE 0 - 35C

SPEAKER Buzzer

BUTTONS Power and reset to default

REMOTE POWER ON/OFF

Through USB-C Charging cable

MOUNTING Microphone stand thread (female 5/8"-27) Mounting Accessory Adapter for mounting to standard tripods (1/4-20 UNC and 3/8"-16 threads).