

HD/SD 6-CHANNEL
SE-2200



Visualise Your Message

The SE-2200 6 input multi-definition switcher is perfect for live production, religious worship, meetings or conference purposes.

It is a technically smart and cost effective portable broadcast-quality switcher.

SE-2200 is a solution that comes with a great features such as 6x6 SDI genlocked Matrix, Dual PIP and built-in title overlay system that works with entry level Datavideo CG systems, or other graphics programmes

The ability to accept up to 6 HD or SD SDI and two HDMI signals, 6 HD or SD SDI assignable outputs and two HDMI multi-view outputs make it a very effective switcher.







**MAKE A
VISUAL IMPACT**





SE-2200 consists of 6 HD/SD-SDI video inputs or with a combination of 4 HD/SD-SDI and 2 HDMI inputs; all of the inputs are reassignable, thus it is able to adapt to your needs. One of the HDMI inputs can be used to accept video from a PC/Laptop computer to work with built-in title overlay system such as Datavideo's CG solutions, including CG-200



Model Name	SE-2200
Product Name	HD/SD 6-Channel Digital Video Switcher
Video Standard	HD & SD
Video Format	1080i 50/59.94/60Hz 720p 50/59.94/60 Hz 576i 50Hz, 480i 59.94Hz
Video Processing	SDI: 4:2:2 HDMI: YUV 4:2:2 10 bit, RGB 4:4:4
Input Routable / Crosspoint	All 6, repeatable
Video Input	6x HD-SDI, 2x HDMI (on CH5 & 6)
Mix HD & SD source	N/A
Computer Graphic Interface	2 via HDMI
Video output	6x SDI Outputs assignable: AUX 1-4, PGM, PVW, PGM Clean & multi-view 2x HDMI assignable: PGM or multi-view
Down-converted output	N/A
Built-in Multi-view monitoring out	2x HDMI
Audio input	4x Balanced XLR
Audio output	2x Balanced XLR
Embedded audio support	Input up to 16 channels, Output 4 channels
Audio Delay Calibration	N/A
A+V switching	Yes
Chroma key	N/A
Title Creator	Yes
USK	N/A
DSK	1x DSK support Lumakey & Linear key (Key / Fill)
Picture in Picture	2
Logo Insertion	2 (or 1 logo + 1 clock)
Still Store	6
Effects	FTB, Cut, 8 Wipe with border

Transition Preview	PiP & DSK
Sync / Reference In/Out	Built-in Genlock (internal)
Tally Output	1x D-sub 25pin, dual color
PC Remote Control	Via Ethernet (free Window software) or RS-422 / RS-232
Built-in Audio Mixer	N/A
Special Features	6x 6 Matrix seamless switch, Built in TC-200 CG interface
Chassis	2 units, 2RU rack-mount mainframe
Power	DC 12V 32W
Accessory	CB-60/61/62 (30/50/100m)