

# sachtler



## System aktiv8 flowtech75 MS

**Sachtler system aktiv8 Sideload with flowtech75 aktiv tripod, mid-level spreader, carry handle and bag**

SKU: S2068S-FTMS

### **Sachtler System aktiv8 flowtech75 with sideload and mid-level spreader**

Weighing only 6.3 kg (13.9 lbs.) the aktiv8 flowtech75 system is both lightweight and durable, designed to be a long-serving and high-performing part of your kit. This system is the perfect choice for professional medium-sized camcorders and digital cine camera set ups of up to 12 kg (26.5 lbs.). 15 counterbalance steps allow for fast and precise balancing of your camera. Its sideload mechanism with a long sliding range of 120 mm make loading and positioning the camera quick and easy. Seven drag settings provide smooth and fast options to adjust drag performance without jolts or vibrations. The illuminated PrismBubble with top or side view makes levelling easy from any height.

### **Fluid Head**

The aktiv8 fluid head with the unique SpeedLevel™ technology can be levelled in seconds giving you time to get the perfect shot in documentary, corporate, or news applications. The SpeedSwap™ system delivers the fastest way to switch between tripod and slider in seconds giving you ultimate flexibility.

### **Tripod**

Capture the widest range of shots in the shortest time with aktiv8 combined with flowtech®75 aktiv. With no bowl clamp required, flowtech can go flat to the ground for extreme low-angle shots – using the versatile hinge lock mechanism of flowtech. The system delivers the widest height range. The 2-stage carbon fibre flowtech tripod with high torsional stiffness has unique quick release brakes which can be deployed and adjusted in an instant. Its ergonomic design makes the tripod comfortable to carry, on shoulder or carry handle, no matter where your creativity takes you. flowtech comes with a quick attach rubber foot mechanism and an adjustable mid-level spreader. When you are ready to move on, the legs are hold together by a magnetic lock for transportation.

**aktiv8 fluid head tripod systems** include the new improved **flowtech®75 aktiv tripod** for optimum performance.

---

## Technical specifications

Feature	Metric	Imperial
<b>Range</b>	aktiv	aktiv
<b>Pan bar count</b>	1	1
<b>Payload</b>	0 to 12 kg	0 to 26.40 lb
<b>Bowl size</b>	75 mm	75 mm
<b>Weight</b>	6.30 kg	13.86 lb
<b>Spreader type</b>	Mid-level spreader	Mid-level spreader
<b>Material</b>	Carbon Fibre	Carbon Fibre
<b>Transport length</b>	850 mm	33.15 in
<b>Tripod stages</b>	2	2
<b>Height Range without spreader</b>	0.23 to 1.70 m	0.75 to 5.58 ft
<b>Height With Mid Spreader</b>	0.79 to 1.74 m	2.59 to 5.71 ft
<b>Temperature range</b>	-40 to 60 °C	-40 to 140 °F
<b>Tilt range</b>	90° to -70°	90° to -70°
<b>Sliding range</b>	120 mm	4.68 in
<b>Interface Compatibility</b>	Sideload	Sideload
<b>Counterbalance</b>	15 + 0 counterbalance steps	15 + 0 counterbalance steps
<b>Drag</b>	7 + 0 drag settings	7 + 0 drag settings

## What's in the box?

aktiv8 fluid head with Sideload plate S and one pan bar DV 75 right; flowtech75 aktiv tripod with carry handle, attachment mount and mid-level spreader; flowtech padded bag

- **Tripod flowtech® 75 aktiv MS**
- **Padded bag flowtech®75**
- **Carry handle flowtech, rotating**
- **aktiv8**

## Data sheets

