



PROFESSIONAL CAMCORDER

Ciptakan kreasi dalam satu genggamannya yang sempurna. Perkarya makna kreasimu dengan kekayaan fitur dari camcorder profesional Canon. Nikmati sensasi ketajaman kualitas dari camcorder Canon. Saatnya kualitas yang bicara.

CANON XF Series

XF300/XF305



- Sensor: 1/3-inch x 3CMOS
- Format: MPEG-2 Long GOP 4:2:2 (50 mbps)
- Recording media: CF card double slot
- Zoom/ 35 mm equivalent focal length: optical 18 x (29.3 - 527.4 mm); f/1.6 - 2.8
- Image stabilization: SuperRange optical (lens shift)

- LED panel: 4.0-inch (1,230,000 dots)
- Bitrate: 50/35/25 mbps; frame rate: 1080-50i/ 25P. 720-50P/ 25P
- Audio: 48 kHz 16-bit 2-channel, linear PCM
- Terminals ports: HD/ SD-SDI (XF305), genlock (XF305), TC (In/Out) (XF305), HDMI, XLR, USB, remote (LANC compatible), AV, component
- Slow & fast motion, interval shooting

Ref. No. XF300
XF305

XF200/XF205



- Sensor: 1/2.84-inch HD CMOS
- Format: MPEG-2 Long GOP 4:2:2 (50 mbps) & MP4
- Recording media: 2 CF card slot + 1 SD card slot
- Zoom/35 mm equivalent focal length: 26.8 mm wide, 20 x optical zoom lens
- Image stabilization: Five-Axis Dynamic Super Range OIS system

- LED panel: 3.5-inch, 1.23 megapixels OLED panel
- Instant AF, face detection; slow, fast motion shooting & interval shooting
- Bitrate: 50/ 35/ 25/ 24/ 17/ 9/ 3/ 1.5 mbps
- Frame rate: 1080-50i/ 25P. 720-50P/ 25P
- Audio: 4-channel 48 kHz 16-bit 2-channel, linear PCM
- Terminals ports: 3G-SDI, HD/ SD-SDI, TC (in/out), genlock (XF205)
- Infrared, GPS, WiFi, LAN terminal

Ref. No. XF200
XF205

XF100/XF105



- Sensor: 1/3-inch, 2.37 megapixels CMOS
- Format: MPEG-2 Long GOP 4:2:2 (50 mbps)
- Recording media: CF card double slot
- Zoom/ 35 mm equivalent focal length: optical 10 x / 30.4 - 304 mm
- Image stabilization: yes
- LCD panel: 3.5-inch 920,000 dots

- Auto focus: instant and medium-speed AF
- Bitrate: 50/ 35/ 25 mbps
- Frame rate: 1080-50i/ 25P. 720-50P/ 25P
- Audio: 48 kHz 16-bit 2-channel, linear PCM
- Terminals ports: HD/ SD-SDI (XF105), genlock (XF105), TC (in/out) (XF105), HDMI, XLR, USB, remote (LANC compatible), AV
- Slow & fast motion, interval shooting: yes

Ref. No. XF100
XF105

XA10/XA20/XA25



- Sensor: 1/3-inch, 2.37 megapixels HD CMOS (XA10)
- Sensor: 1/2.84-inch, 3.09 megapixels HD CMOS (XA20 & XA25)
- Optical zoom 10 x (XA10)
- Optical zoom 20 x (XA20 & XA25)
- Image stabilization
- LCD panel: 3.5-inch touch panel LCD screen
- Cinema look filter

- Recording format: AVCHD (H.264), MP4 (AAC/H.264) (XA20 & XA25)
- Built-in memory 64 GB (XA10) & 2 slot SD card
- Genlock or timecode HD, SD-SDI terminal (XA25)
- Mini HDMI, AV cable terminal
- Built-in Wi-Fi (XA20 & XA25)
- Manual & professional control

Ref. No. XA-10
XA-20
XA-25